



PRO4600

Key Features :

- 2x 2600W/2 Ω , 2x 2300W/4 Ω , 2x 1400W/8 Ω , Bridge mode 5200 W/4 Ω
- Soft resonant switching power supply with active Power Factor Correction PFC
- Stereo, Mono or Bridge mode operation (switch on the rear)
- XLR balanced input- and professional SPEAKON output- connectors
- Fully automatic protections against direct current, over heat, over load, on/off switching RF and amplitude limit
- Variable speed fan controller with temperature sensor
- Efficient power consumption
- Carefully selected high quality components
- 2 years warranty

Specification :

- Input sensitivity : 0.775V
- Input impedance(nominal) : 10K ohms/20K ohmsr
- Power Delay : 4 seconds
- Frequency Response : 10Hz to 20k Hz,+/-1dB
- Total harmonic Distortion (THD) : <0.05%
- Slew Rate : $\geq 20\text{v}/\mu\text{S}$
- Cross Talk : 40dB
- Damping Factor : >600 (8ohm),10Hz-400Hz
- S/N Ratio (20Hz-20Khz,4 Ohms) : $>106\text{dBA}$
- Input Interface : XLR input socket
- Output Interface : SPEAKON connector
- Dimensions (WxHxD) : 483x44x230mm
- Weight : 7.50kg