

Data Sheet

FBT S215LSZH / S225LSZH



Colours may vary. Image for illustration purpose only.

Type: **Speaker cable LSZH**

Description: Flexible stranded conductors insulated with halogen free compound, twisted cores, under a halogen free compound.

Voltage Rating (V): 300

Test Voltage (kV): 2,5

Minimum operating temperature: -25° C (without mechanical stress-fixed installation)

Minimum installation temperature: 5°C

Maximum operating temperature: 70°C

Resistance at 20 °C (Ohm/Km): According to standard IEC 228/HD 383 S2

Resistance to flame propagation: According to the standard IEC 30332-1-2

Halogen-free: EN 50525-1, EN 50267-2-2, EN 50267-2-1, EN 60884-2

Cod.	Sec. n x	Conductor mm	Insulati	Ø core mm ±0,15	Jacket	External Ø mm
S215HF	2x1,5	Class 5 CU 0,25	Hal. free	2,3	Hal. free	5,8
S225HF	2x2,5	Class 5 CU 0,25	Hal. free	3,0	Hal. free	7,0

- ☐ Conductor: Bare stranded Copper
- ☐ Conductor: Class 5 according to standard IEC 60228/HD 383 S2
- ☐ Insulation colour: on request
- ☐ Sheath colour: Black

Standard References

BT 93/68 CEE

2014/35/EU

2011/65/CE (RoHS II)

2006/1907/CE (Reach)



The information contained in this document has been carefully checked for accuracy, however no guarantee is given with respect to the correctness. The firm does not make any representations or warranties (implied or otherwise) regarding the accuracy and completeness of this document and shall in no event be liable for any loss of profit or any commercial damage, including but not limited to special, incidental, consequential, or other damage Specifications and information contained in this document are subject to change at any time without notice.