

Data Sheet

FBT DMX2025



Colours may vary. Image for illustration purpose only.

Customer: FBT Audio (UK) Limited

Type: **DMX**

Description: **DMX cable.**
Flexible cable insulated in PE under PVC soft sheath.

Voltage Rating (V): 100

Test Voltage (kV): 2,0

Minimum operating temperature: -30° C (without mechanical stress-fixed installation)

Minimum installation temperature: 5°C

Maximum short circuit temperature: 60°C

Resistance at 20 °C (Ohm/Km): According to standard IEC 228/HD 383 S2

Resistance to flame propagation: According to the standard IEC 30332-1-2

Sec. n x mm ²	Conductor n x mm	Conductor n x mm	Insulation	Nom. Core Ø mm ± 0,15	Shield	Sheath	Overall Ø mm ± 0,15
2x0,25	Bare copper	14x0,25	PE	1,80	Aluminium/PET foil + Tinned copper shield	Soft PVC	5,4

- Conductor: Stranded bare copper
- Conductor: Class 5 according to standard IEC 60228/HD 383 S2
- Insulation colour: on request
- Sheath colour: black

Standard References

BT 93/68 CEE

2014/35/EU

2011/65/CE (RoHS II)

2006/1907/CE (Reach)

